

WHAT IS CLAIMED IS:

1. A method for maintaining synchronization between an incoming transport stream and a program stream decoder during a conversion of the transport stream to a program stream, comprising the steps of:
- 5 calculating a system clock reference (SCR) from the transport stream;
calculating a multiplexer-rate for the program stream; and
forming the program stream by multiplexing packetized elementary stream (PES) packets corresponding to the transport stream using the multiplexer-rate.
- 10
2. The method of claim 1, further comprising the step of managing time discontinuities during the conversion, wherein said managing step comprises the steps of:
- 15 detecting an SCR discontinuity; and
discarding a current pack and adding a system header to a subsequent pack to inform the decoder to adjust an internal reference clock to be synchronized, when the decoder uses the system header to reset the internal reference clock.
- 20
3. The method of claim 1, further comprising the step of managing time discontinuities during the conversion, wherein said managing step comprises the steps of:
- 25 detecting an SCR discontinuity; and
disabling time-stamp decoding by the decoder across the SCR discontinuity to reset an internal reference clock of the decoder, when the decoder does not use a system header to reset the internal reference clock.
4. The method of claim 3, wherein said disabling step comprises the step of toggling a low delay mode of the decoder on and off at the SCR discontinuity.
- 30

5. The method of claim 1, further comprising the step of including a number of bytes dropped between packets in the transport stream when performing said step of calculating the SCR.

5 6. The method of claim 1, wherein said step of calculating the SCR comprises the steps of:

computing a delta time as a difference between program clock reference (PCR) values of the transport stream;

10 computing a transport rate as a number of bytes between PCRs divided by the delta time; and

computing the SCR as a number of bytes between a unit-start packet and a PCR packet divided by the transport rate, plus a PCR prior to unit-start.

15 7. The method of claim 1, wherein said step of calculating the multiplexer-rate comprises the steps of:

computing a delta SCR as a difference between an SCR at end of Pack and an SCR at start of Pack; and

20 computing the multiplexer-rate as the product of a number of bytes to output and 27,000,000 ticks, divided by 50 bytes, and divided by the delta SCR.

8. The method of claim 1, wherein the transport stream comprises at least one packet having an extended time stamp, the extended time stamp specifying a value that corresponds to an actual delivery time for a predetermined byte.

25 9. The method of claim 8, wherein said step of calculating the SCR comprises the step of computing the SCR as a delta time at unit start divided by a delta time to current packet, plus a PCR prior to unit start.

10. The method of claim 8, wherein said step of calculating the multiplexer-rate comprises the steps of:

computing a delta SCR as a difference between an SCR at end of Pack and an SCR at start of Pack; and

5 computing the multiplexer-rate as the product of a number of bytes to output and 27,000,000 ticks, divided by 50 bytes, and divided by the delta SCR.

11. The method of claim 8, further comprising the step of adding a time-stamp to each transport packet that specifies a time at which a first packet
10 byte was received and using the time-stamp in performing said step of calculating the SCR.

12. A device for maintaining synchronization between an incoming transport stream and a program stream decoder during a conversion of the
15 transport stream to a program stream, comprising:

means for calculating a system clock reference (SCR) from the transport stream;

means for calculating a multiplexer-rate for the program stream; and

20 means for forming the program stream by multiplexing packetized elementary stream (PES) packets corresponding to the transport stream using the multiplexer-rate.

13. The device of claim 12, further comprising means for managing time discontinuities during the conversion.

14. The device of claim 13, wherein said means for managing time discontinuities comprises:

means for detecting an SCR discontinuity; and

30 means for discarding a current pack and adding a system header to a subsequent pack to inform the decoder to adjust an internal reference clock to be synchronized, when the decoder uses the system header to reset the internal reference clock.

15. The device of claim 13, wherein said means for managing time discontinuities comprises:

means for detecting an SCR discontinuity; and

means for disabling time-stamp decoding by the decoder across the
5 SCR discontinuity to reset an internal reference clock of the decoder, when the decoder does not use a system header to reset the internal reference clock.

16. The device of claim 15, wherein said means for disabling time-
stamp decoding toggles a low delay mode of the decoder on and off at the SCR
10 discontinuity.

17. The device of claim 12, wherein said means for calculating the
SCR includes a number of bytes dropped between packets in the transport
stream when calculating the SCR.
15

18. The device of claim 12, wherein the transport stream comprises at
least one packet having an extended time stamp, the extended time stamp
specifying a value that corresponds to an actual delivery time for a
predetermined byte.
20

19. The device of claim 18, further comprising means for adding a
time-stamp to each transport packet that specifies a time at which a first packet
byte was received, and wherein said means for calculating the SCR uses the
time-stamp in calculating the SCR.
25

20. A device for translating a transport stream to a program stream,
comprising:

an isochronous delivery system for providing the transport stream; and

a program stream decoder for calculating a system clock reference

(SCR) from the transport stream, calculating a multiplexer-rate for the program
stream, and forming the program stream by multiplexing packetized elementary
stream (PES) packets corresponding to the transport stream using the
multiplexer-rate.
30

21. A device for transcoding an MPEG transport stream into an MPEG program stream, comprising:

a parser for parsing packetized elementary stream (PES) packets from the transport stream;

5 a PES filter for passing and buffering selected ones of the parsed PES packets; and

a packet assembler for accessing and multiplexing the buffered selected ones of the parsed PES packets to form the MPEG program stream.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995